

## SBG8300

### DOCSIS 3.1 Consumer Series Wireless Cable Modem

#### FEATURES

- DOCSIS 3.1 and DOCSIS 3.0 capable
- DOCSIS 3.1 supports 10+ Gbps Download
- Multiple 4k, virtual reality, and HD video streams easily supported
- 2x2 OFDM and OFDMA DOCSIS® 3.1 channels
- 32x8 SC-QAM DOCSIS® 3.0 channels
- Full Capture Bandwidth Tuner
- Multi Processor Technology with ARM and ATOM based Application Processors
- 4 port Gigabit Ethernet Router
- 4x4 Integrated Dual Band Concurrent 5GHz Wi-Fi 5 radios and 3x3 2.4GHz 802.11n for high performance WLAN
- Primary, secondary and guest SSIDs
- Designed for enhanced management via SURFboard Mobile Manager and Amazon Alexa voice commands



#### PRODUCT OVERVIEW

The SBG8300 Wireless Gateway, supporting DOCSIS 3.1 standards, allows unprecedented data rates to be delivered to cable subscribers. Designed to support Gigabit + services while also providing secure internet connections and powerful parental controls, the SBG8300 also offers superior Wi-Fi performance enabling fast and reliable home networking coverage using 802.11ac wave 2 technology.

This feature-packed unit is intended to serve as the hub of the home or small business network, connecting all IP capable devices (Internet, Data, and Streaming Video) throughout the premises.

## Product Highlights

### Easy to Setup and Use

- Plug-and-play installation, use the SURFboard Manager App on your mobile device for management (including remote management when you are away from home)
- Use Alexa voice commands via an Amazon Alexa enabled device 'Ask SURFboard' to manage your network.
- Default settings for recommended Security and Quality of Service protection supports standard Internet browser software
- Front panel status LEDs indicate connectivity and simplify troubleshooting.
- User-friendly online, mobile app, or Amazon Alexa based diagnostics and configuration

### Advanced Services Ready

- DOCSIS 3.1 Gigabit services ready supporting 2x 196 MHz OFDM and 2x 96 MHz OFDMA channels
- Channel bonding of up to thirty-two downstream and eight upstream channels in DOCSIS 3.0 mode
- Internet connectivity in the received (downstream) data stream of over 10 Gbps
- 108 -1002 MHz Full Capture Bandwidth Tuner
- Supports both IPv4 and IPv6
- Integrated 2.4 GHz 802.11n and 5 GHz 802.11ac Wi-Fi® access point, concurrent radio operation with Wi-Fi 5 MIMO support
- 3x3 and 4x4 MIMO antenna arrays offer performance benefits for wireless LAN (WLAN) access points
- Powerful Wi-Fi® output added for optimized throughput over a greater range
- Four 1 Gb Ethernet ports enable flexible, high-speed connectivity with Auto Negotiate and Auto MDIX
- Support for Multicast IP services

### Reliable and Secure

- WPA/WPA2 Wi-Fi® security
- Supports AES traffic encryption

### Benefits

- Top of the line Cable Modem Wireless Access Point using 802.11ac wave 2 wireless technology, supporting 2350 Mbps throughput
- Supported by ARRIS's highly rated Consumer Support Team
- Supports Energy Efficient Ethernet on the 4x GigE ports

For information on additional  
SURFboard products please visit  
[www.SURFboard.com](http://www.SURFboard.com)

For product support please visit  
[www.arris.com/consumers](http://www.arris.com/consumers)

## SPECIFICATIONS

### Physical

Operating Temperature	0 to 50°C
Operating Relative Humidity	5-85% (Non condensing)
Storage Temperature	-40 to 70°C
Dimensions (H x W x D)	9.33in x 2.87in x 8in 237mm x 73mm x 205mm
Weight	1.94lbs 0.88kg
Diagnostic LED's (Front)	Integrated LED for status of Power, US/DS, Online, 2.4GHz, 5GHz,
Diagnostic LED's (Rear)	Ethernet Link/Speed

### RF Downstream

Bonded Channels	Up to 32 SC-QAM or 2 OFDM
Tuner Configuration	Full capture tuning range
Frequency Range (MHz)	108MHz - 1002MHz DOCSIS
Data Rate* (Mbps Max.)	Up to 4Gbps (limited by 4x Enet ports)
RF Input Sensitivity Level	-15dBmV to +15dBmV (DOCSIS)

### RF Upstream

Bonded Channels	Up to 8 SC-QAM or 2 OFDMA
Frequency Range	5MHz to 85MHz
Configurable Diplex Filter	42MHz-85MHz
Data Rate* (Mbps Max.)	Up to 1Gbps
RF Output Level	+65 dBmV (64 QAM, single upstream) +57 dBmV (64 QAM, 4-8 upstreams) +65 dBmV (16 QAM, single upstream)

\*Max raw DOCSIS rate; actual throughput is less due to overhead, configuration, and RF conditions. Max Rate may also be limited by service level from the ISP.

**Copyright Statement:** © 2019 ARRIS Enterprises LLC. All rights reserved. No part of this publication may be reproduced in any form or by any means or used to make any derivative work (such as translation, transformation, or adaptation) without written permission from ARRIS Enterprises, LLC ("ARRIS"). ARRIS reserves the right to revise this publication and to make changes in content from time to time without obligation on the part of ARRIS to provide notification of such revision or change. ARRIS, SURFboard and the ARRIS logo are all registered trademarks of ARRIS Enterprises, LLC. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks or the names of their products. ARRIS disclaims proprietary interest in the marks and names of others.

**Note:** The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice.



## SPECIFICATIONS

### Interfaces

RF Interface	1 External 'F' type connector
Date Interfaces (bridged)	4 x 10/100/1000 Base-T Ethernet (RJ-45 connector) MDI /MDI-X
Input Voltage (nominal)	12V DC
AC-DC	External

### Wireless

Frequency Range	Dual Band Concurrent 2.4GHz and 5GHz
Standard	802.11ac Wave 2
Wi-Fi throughput	AC2350
Transmit Power (from any antenna)	+27 dBm (MCS7) +26 dBm (MCS9)
Antenna: Spatial Streams	2.4GHz = 3x3:3 5GHz= 4x4:
Receive Levels	2.4GHz <-88dBm 802.11n (MCS0) , <-71dBm 802.11n (MCS7), HT20 5.0GHz <-84dBm 802.11ac (MCS0) , <-57dBm 802.11ac (MCS9), VHT80